

lammina

10UL

Ultra Light Aluminum Tenders



	Overal Length	•	10'/ 3.05m	Number of Chambers	:	3	Shaft Length	:15″/38.1cm
S P E C S	Overal Beam	:	5'6"/ 1.68m	Person Capacity	:	5	RDC Design Category	:с
	Inside Length	:	7′2″/ 2.18m	Weight	:	95lb / 43kg		
	Inside Beam	:	2′8″/ 0.81m	Recommended HP	:	9.9hp / 7.4kw		
	Tube Diameter	:	17″/ 0.43m	Maximum HP	:	15hp / 11.2kw		

- Shallow "V" Marine Grade Aluminum Hull
 Transom Knee
- Non-Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate With Security Lip

ND

ωш

A R

 $\Box \supset$

zΗ

 $\triangleleft \triangleleft$

⊢ш чг

л v ∢ш Zœ

0⊃

- H

⊢∢ പപ Ош

- Aluminum Bow Eye 3 Aluminum Davit Lifting Points Aluminum Bow Towing Rings Aluminum Bow Towns
 Deck Drain with Plug

- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 France Push Plastic Non-Corrosive 2 Stage Inflation Valves
 France Version Plastic Non-Corrosive 2 Stage Inflation Valves
 France Version Plastic Non-Corrosive 2 Stage Inflation Valves
 France Version Plastic Non-Corrosive 2 Stage Inflation Valves
 Maintenance Kit
 Inside Bow Sets of Double Orca (CSM) Fabric Handles on Tubes
 Owner's Manual
 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
 Stage Reinforced Seams
 Coarlock Bases
- Telescopic Oars with Aluminum ShaftPaddle Holders
- Hand Pump

- Tube Chaps
- Boat Cover
- Chock Set



Orca (CSM) Five Layer Coated Fabric Raised Single Rub Rail