2



## lammina

11AL SUPERLIGHT

## **Aluminum Tenders**



Overal Length	11'6"/ 3.50m Number of Cham	bers : 3	Maximum HP	: 30hp / 22.4kw
Overal Beam	5'7"/ 1.70m Person Capacity	: 6	Shaft Length	: 20" / 50.8cm
Inside Length	8'6"/ 2.60m Weight	: 172lb / 78kg	RDC Design Category	: C
Inside Beam	2'8"/ 0.81m Weight with Bow I	ocker: 187lb/85kg		
Tube Diameter	17"/ 0.43m Recommended H	P : 20hp /14.9kw		

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Heavy Duty Transom Knee Non Skid Rubber Floor Panels Plastic External Transom Plate
- Aluminum Internal Transom Plate
- Aluminum Bow Eye
- 3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings

- Deck Drain with Plug
  Orca(CSM) Five Layer Coated Fabric
  Raised Single Solid Rub Rail
  Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
  Maintenance Kit
- 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Single Orca (CSM) Fabric Handles on Tube
- Removable Stern Seat
- Paddles with Aluminum Shaft

- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

- Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank
- Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings
- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat
- Fiberglass Console with Forward Seat

- Fiberglass Console
- Bench Seat with Storage
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit

