

# ventus

12VL

Lightweight Fiberglass Tender

OPTIONAL BOW STEP



S P E C S

|                |                 |                    |                 |                     |                |
|----------------|-----------------|--------------------|-----------------|---------------------|----------------|
| Overall Length | : 12' / 3.66m   | Number of Chambers | : 3 + 1         | Shaft Length        | : 15" / 38.1cm |
| Overall Beam   | : 5'11" / 1.77m | Person Capacity    | : 6             | RDC Design Category | : C            |
| Inside Length  | : 8'9" / 2.67m  | Weight             | : 156lb / 71kg  |                     |                |
| Inside Beam    | : 2'9" / 0.84m  | Recommended HP     | : 20hp / 14.9kw |                     |                |
| Tube Diameter  | : 18" / 0.46m   | Maximum HP         | : 30hp / 22.4kw |                     |                |

S T A N D A R D  
F E A T U R E S

- Hand Laid Fiberglass Deep "V" Hull
- Stringer System Laminated into Hull
- Non - Skid Rubber Floor Pannels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate with Security Lip
- Stainless Steel Bow Eye
- Stainless Steel 3 Davit Lifting Points
- Inner Hull Drain with Plug
- Deck Condensation Plug
- Orca(CSM) Five Layer Coated Fabric
- Raised Single Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of 2 Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Single Orca(CSM) Fabric Handles on Tubes
- Removable Stern Seat
- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- Additional Air Retaining Chamber Under the Floor
- 3 Layer Reinforced Seams

O P T I O N A L  
F E A T U R E S

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat

