navigo

13VS

Open FiberglassTenders



Overal Beam Inside Length

Overal Length

: 13'/ 3.96m

: 9'9"/ 2.97m

Number of Chambers : 3 + 1

Weight

Shaft Length : 20" / 50.8cm

: 6'4"/1.94m

Person Capacity : 7 RDC Design Category : C

Inside Beam : 3'1"/ 0.94m

Recommended HP

: 30hp / 22.4kw

: 293lb / 133kg

Tube Diameter : 18"/ 0.46m Maximum HP : 40hp / 29.8kw

A R ∢ < \vdash \sqcup SH

Δш 0 н

ے

S

- Hand Laid Fiberglass Deep "V" Hull
- Stringer System Laminated into Hull Bow Locker/ Seat
- Diamond Shape Non Skid Deck
- Plastic External Transom Plate

- Aluminum Internal Transom Plate
 Orca (CSM) Five Layer Coated Fabric
 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

 ■
- Raised Double Rub Rail Stainless Steel Bow Eye

- 4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug
- Deck Drain with Plug
- 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes
 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes
 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams
- Paddle with Aluminum Shaft
- Paddle Holders

- Removable Stern SeatHand Pump
- Maintenance Kit Owner's Manual
- Additional Air Retaining Chamber Under the Floor

- Bow Hatch Cushion
- Boat Cover
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat

- Bimini Top
- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit

