

lammina

14AL SUPERLIGHT

Aluminum Tenders



S P E C S	Overall Length	: 14' / 4.27m	Number of Chambers	: 4	Maximum HP	: 50hp / 37.3kw
	Overall Beam	: 6'7" / 2.00m	Person Capacity	: 8	Shaft Length	: 20" / 50.8cm
	Inside Length	: 10'10" / 3.30m	Weight	: 246lb / 112kg	RDC Design Category : C	
	Inside Beam	: 3'3" / 0.99m	Weight with Bow Locker : 264lb / 120kg			
	Tube Diameter	: 19" / 0.48m	Recommended HP : 40hp / 29.8kw			

STANDARDS
FEATURES

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Heavy Duty Transom Knee
- Non - Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate
- Aluminum Bow Eye
- 3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings

- Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
- Orca(CSM) Five Layer Coated Fabric
- Raised Double Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of Triple Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes

- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

OPTIONAL
FEATURES

- Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank
- Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings
- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Fiberglass Console
- Fiberglass Console with Forward Seat

- Bench Seat with Storage
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit

