lammina

15AL SUPERLIGHT

Aluminum Tenders



Overal Beam Inside Length

Inside Beam

: 15'/ 4.57m : 6'9"/ 2.06m **Number of Chambers**

: 339lb/154kg

Maximum HP : 60hp / 44.8kw

Person Capacity : 9 Shaft Length : 20" / 50.8cm

RDC Design Category : C

: 11'8"/3.55m

: 3'4"/ 1.03m

Weight with Bow Locker: 357lb/162kg

: 19"/ 0.48m Tube Diameter

Recommended HP : 50hp/37.3kw

2 ж ш A A ∢ ∢ \vdash \sqcup SH

 \sim

 \circ

Δш

0 ш

⋖

ے

S

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Heavy Duty Transom Knee Non Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate
- Aluminum Bow Eye
- 3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings

Weight

- Deck Drain with Plug
 Orca(CSM) Five Layer Coated Fabric
 Raised Double Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of Quadruple Orca(CSM) Fabric Handles on Tubes
 Rubber Protector on Full Length of Keel
- 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams

- Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank
- Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings
- Tube Chaps
- Boat Cover
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Fiberglass Console
- Fiberglass Console with Forward Seat

- Bench Seat with Storage
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit

