

lammina

8 AL SUPERLIGHT

Aluminum Tenders



S P E C S	Overall Length	: 8'5" / 2.56m	Number of Chambers	: 3	Maximum HP	: 6hp / 4.5kw
	Overall Beam	: 4'9" / 1.45m	Person Capacity	: 4	Shaft Length	: 15" / 38.1cm
	Inside Length	: 5' 10" / 1.79m	Weight	: 73lb / 33kg	RDC Design Category : C	
	Inside Beam	: 2' / 0.62m	Weight with Bow Locker	: 80lb/36kg		
	Tube Diameter	: 16" / 0.41m	Recommended HP	: 4hp / 3.0kw		

STANDARDS FEATURES	<ul style="list-style-type: none">■ Deep "V" Marine Grade Aluminum Hull■ Heavy Duty Transom Knee■ Non - Skid Rubber Floor Panels■ Plastic External Transom Plate■ Aluminum Internal Transom Plate with Security Lip■ Aluminum Bow Eye■ 3 Aluminum Davit Lifting Points■ Deck Drain with Plug	<ul style="list-style-type: none">■ Orca(CSM) Five Layer Coated Fabric■ Push Push Plastic Non-Corrosive 2 Stage Inflation Valves■ Raised Single Rub Rail■ 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes■ 2 Inside Bow Single Orca(CSM) Fabric Handles on Tubes■ 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes■ Removable Rowing Seat■ Oarlock Bases	<ul style="list-style-type: none">■ Telescopic Oars with Aluminum Shaft■ Paddle Holders■ Hand Pump■ Maintenance Kit■ Owner's Manual■ 3 Layer Reinforced Seams■ Rubber Protector on Full Length of Keel
-----------------------	---	--	--

OPTIONAL FEATURES	<ul style="list-style-type: none">■ Bow Locker Storage with Vent to Fit a 3 Gal Portable Fuel Tank■ Tube Chaps■ Boat Cover	<ul style="list-style-type: none">■ Lateral Fold Down Stainless Steel Cleat■ Chock Set■ Bow Step with Fold Down Stainless Steel cleat
----------------------	--	---

