

lammina

9UL

Ultra Light Aluminum Tenders



S P E C S	Overall Length	: 9'1" / 2.76m	Number of Chambers	: 2	Shaft Length	: 15" / 38.1cm
	Overall Beam	: 4'11" / 1.50m	Person Capacity	: 4	RDC Design Category	: C
	Inside Length	: 6'3" / 1.90m	Weight	: 75lb / 34kg		
	Inside Beam	: 2'3" / 0.70m	Recommended HP	: 8hp / 6kw		
	Tube Diameter	: 16" / 0.41m	Maximum HP	: 10hp / 7.5kw		

STANDARD FEATURES	<ul style="list-style-type: none">Shallow "V" Marine Grade Aluminum HullNon-Skid Rubber Floor PanelsPlastic External Transom PlateAluminum Internal Transom Plate With Security LipAluminum Bow Eye3 Aluminum Davit Lifting PointsAluminum Bow Towing RingsDeck Drain with PlugOrca (CSM) Five Layer Coated FabricRaised Single Rub RailPush Push Plastic Non-Corrosive 2 Stage Inflation Valves1 Front & Side Orca (CSM) Fabric Handles on Tubes2 Inside Bow Single Orca (CSM) Fabric Handles on Tubes2 Inside Stern Single Orca (CSM) Fabric Handles on TubesRemovable Rowing SeatOarlock BasesTelescopic Oars with Aluminum ShaftPaddle HoldersHand PumpMaintenance KitOwner's Manual3 Layer Reinforced Seams
----------------------	---

OPTIONAL FEATURES	<ul style="list-style-type: none">Tube ChapsBoat CoverChock Set
----------------------	---