

ventus

9VL

Lightweight Fiberglass Tender

OPTIONAL BOW STEP



S P E C S	Overall Length	: 9'6" / 2.90m	Number of Chambers	: 3 + 1	Shaft Length	: 15" / 38.1cm
	Overall Beam	: 5'7" / 1.72m	Person Capacity	: 4	RDC Design Category	: C
	Inside Length	: 6'9" / 2.06m	Weight	: 106lb / 48kg		
	Inside Beam	: 2'8" / 0.81m	Recommended HP	: 9.9hp / 7.4kw		
	Tube Diameter	: 17" / 0.43m	Maximum HP	: 15hp / 11.2kw		

STANDARD
FEATURES

- Hand Laid Fiberglass Deep "V" Hull
- Stringer System Laminated into Hull
- Non - Skid Rubber Floor Pannels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate with Security Lip
- Stainless Steel Bow Eye
- Stainless Steel 3 Davit Lifting Points
- Inner Hull Drain with Plug

- Deck Condensation Plug
- Orca(CSM) Five Layer Coated Fabric
- Raised Single Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of 2 Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Single Orca(CSM) Fabric Handles on Tubes
- Removable Rowing Seat

- Oarlock Bases
- Telescopic Oars with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- Additional Air Retaining Chamber Under the Floor
- 3 Layer Reinforced Seams

OPTIONAL
FEATURES

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat

- Lateral Fold Down Stainless Steel Cleat
- Removable Stern Seat