



S P E C S	Overall Length	: 9'6" / 2.90m	Number of Chambers	: 3 + 1	Shaft Length	: 15" / 38.1cm
	Overall Beam	: 5'7" / 1.72m	Person Capacity	: 4	RDC Design Category	: C
	Inside Length	: 6'9" / 2.06m	Weight	: 143lb / 65kg		
	Inside Beam	: 2'8" / 0.81m	Recommended HP	: 9.9hp / 7.4kw		
	Tube Diameter	: 17" / 0.43m	Maximum HP	: 15hp / 11.2kw		

S T A N D A R D F E A T U R E S	<ul style="list-style-type: none">■ Hand Laid Fiberglass Deep "V" Hull■ Stringer System Laminated into Hull■ Bow Locker/ Seat with Vent■ Bow Locker Storage to Fit a 6 Gal Portable Fuel Tank■ Diamond Shape Non - Skid Deck■ Plastic External Transom Plate■ Aluminum Internal Transom Plate with Security Lip■ Orca (CSM) Five Layer Coated Fabric■ 3 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves■ Raised Single Solid Rub Rail■ Stainless Steel Bow Eye	<ul style="list-style-type: none">■ 4 Stainless Steel Davit Lifting Points■ Stainless Steel Towing Rings & Tie Downs■ Deck Condensation Plug■ Deck Drain with Plug■ 1 Front & 2 Side Orca (CSM) Fabric Handles on Tubes■ 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes■ 2 Inside Stern 1 Orca (CSM) Fabric Handles on Tubes■ 3 Layer Reinforced Seams■ Oarlock Bases	<ul style="list-style-type: none">■ Telescopic Oars with Aluminum Shaft■ Paddle Holders■ Removable Rowing Seat■ Hand Pump■ Maintenance Kit■ Owner's Manual■ Additional Air Retaining Chamber Under the Floor■ Hidden Channel for Fuel Fittings with SS Starburst

O P T I O N A L F E A T U R E S	<ul style="list-style-type: none">■ Portable 6 gal Fuel Tank Installed in Bow Locker with Fittings■ Bow Hatch Cushion■ Tube Chaps■ Boat Cover■ Chock Set	<ul style="list-style-type: none">■ Bow Step with Fold Down Stainless Steel Cleat■ Lateral Fold Down Stainless Steel Cleat■ Removable Stern Seat■ Bimini Top