



S P E C S	Overall Length	: 9'6" / 2.90m	Number of Chambers	: 3	Maximum HP	: 15hp / 11.2kw
	Overall Beam	: 5'6" / 1.68m	Person Capacity	: 5	Shaft Length	: 15" / 38.1cm
	Inside Length	: 6'11" / 2.11m	Weight	: 95lb / 43kg	RDC Design Category : C	
	Inside Beam	: 2'6" / 0.76m	Weight with Bow Locker	: 108lb/49kg		
	Tube Diameter	: 17" / 0.43m	Recommended HP	: 8hp / 6.0kw		

STANDARDS FEATURES	<ul style="list-style-type: none"><li>■ Deep "V" Marine Grade Aluminum Hull</li><li>■ Stringer System Welded Under Aluminum Deck</li><li>■ Heavy Duty Transom Knee</li><li>■ Non - Skid Rubber Floor Panels</li><li>■ Plastic External Transom Plate</li><li>■ Aluminum Internal Transom Plate with Security Lip</li><li>■ Aluminum Bow Eye</li><li>■ 3-4 Aluminum Davit Lifting Points</li><li>■ Aluminum Transom Tie Down &amp; Towing Rings</li></ul>	<ul style="list-style-type: none"><li>■ Deck Drain with Plug</li><li>■ Orca(CSM) Five Layer Coated Fabric</li><li>■ Raised Single Rub Rail</li><li>■ Push Push Plastic Non-Corrosive 2 Stage Inflation Valves</li><li>■ 1 Front &amp; 2 Side Orca(CSM) Fabric Handles on Tubes</li><li>■ 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes</li><li>■ 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes</li><li>■ Removable Rowing Seat</li></ul>	<ul style="list-style-type: none"><li>■ Oarlock Bases</li><li>■ Telescopic Oars with Aluminum Shaft</li><li>■ Paddle Holders</li><li>■ Hand Pump</li><li>■ Maintenance Kit</li><li>■ Owner's Manual</li><li>■ 3 Layer Reinforced Seams</li><li>■ Rubber Protector on Full Length of Keel</li></ul>
-----------------------	--	---	--

OPTIONAL FEATURES	<ul style="list-style-type: none"><li>■ Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank</li><li>■ Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings</li><li>■ Tube Chaps</li><li>■ Boat Cover</li><li>■ Chock Set</li></ul>	<ul style="list-style-type: none"><li>■ Bow Step with Fold Down Stainless Steel Cleat</li><li>■ Lateral Fold Down Stainless Steel Cleat</li></ul>
----------------------	---	---