

Professional Fiberglass Boats

SPECS	Overal Length	:	15′/ 4.57m	Number of Chambers	:	5	Shaft Length	: 20″/50.8cm
	Overal Beam	:	6′6″/ 1.99m	Person Capacity	:	11	Optional Fuel Tank	: 23 Gal / 87 Lt.
	Inside Length	•	11′6″/ 3.50m	Weight	:	484lb / 220kg	RDC Design Category	: C
	Inside Beam	:	3′2″/ 0.97m	Recommended HP	:	60hp / 44.8kw		
	Tube Diameter	:	19"/ 0.48m	Maximum HP	:	75hp / 56kw		

- Professional Grade Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Bow Locker/ Seat
- Diamond Shape Non Skid Deck
- Plastic External Transom Plate Aluminum Internal Transom Plate
- Heavy Duty 1670 Decitex Orca (CSM) Five Layer Coated Fabric Deck Drain with Plug Life Line Around Tube 1 Front & 5 Side Orca (CSM) Fabric Handles on Tubes
- ⊢ш
 - Non Skid (CSM) Coated Fabric on Tube's Surface Pressure Relief Valves
- ~ ш ZĽ

0⊃

⊢∢

ு ய

Оц

- Optional Fuel Tank 23 Gal / 87 L Bow Hatch Cushion
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- **Removable Rowing Seat**

- 4 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves Paddle Holders
- Double Solid Rub Rail Stainless Steel Bow Eye
- 4 Stainless Steel Davit Lifting Points
- Stainless Steel Towing Rings & Tie Downs
- Deck Condensation Plug

- 3 Layer Reinforced Seams
- Paddle with Aluminum Shaft

- Hand Pump
- Maintenance Kit
- Owner's Manual
- Additional Air Retaining Chamber Under the Floor
- Drain Scuppers
 Rubber Protector on Full Length of Keel
- Bimini Top
- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit



ΔS

പ ന

ЧЧ

 $\Box \supset$

zμ

∢∢

νц