



A B I N F L A T A B L E S

lammina

8 AL

SUPERLIGHT

Aluminum Tenders



S P E C S	Overall Length	: 8'5" / 2.56m	Number of Chambers	: 3	Shaft Length	: 15" / 38.1cm
	Overall Beam	: 4'9" / 1.45m	Person Capacity	: 4	RDC Design Category	: C
	Inside Length	: 5' 10" / 1.79m	Weight	: 73lb / 33kg		
	Inside Beam	: 2' / 0.62m	Recommended HP	: 4hp / 3.0kw		
	Tube Diameter	: 16" / 0.40m	Maximum HP	: 6hp / 4.5kw		

STANDARD FEATURES

- Deep "V" Marine Grade Aluminum Hull
- Heavy Duty Transom Knee
- Non - Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate with Security Lip
- Aluminum Bow Eye
- 3 Aluminum Davit Lifting Points
- Deck Drain with Plug

- Orca(CSM) Five Layer Coated Fabric
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Raised Single Rub Rail
- 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Single Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
- Removable Rowing Seat
- Oarlock Bases

- Telescopic Oars with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

OPTIONAL
FEATURES

- Tube Chaps
- Boat Cover
- Chock Set

- Bow Step with Fold Down Stainless Steel cleat
- Lateral Fold Down Stainless Steel Cleat



lammina

9 AL

SUPERLIGHT

Aluminum Tenders



S P E C S	Overall Length	: 9'1" / 2.76m	Number of Chambers	: 3	Shaft Length	: 15" / 38.1cm
	Overall Beam	: 4'9" / 1.45m	Person Capacity	: 4	RDC Design Category	: C
	Inside Length	: 6'3" / 1.90m	Weight	: 79lb / 36kg		
	Inside Beam	: 2'2" / 0.66m	Recommended HP	: 8hp / 6.0kw		
	Tube Diameter	: 16" / 0.40m	Maximum HP	: 10hp / 7.5kw		

S T A N D A R D F E A T U R E S	<ul style="list-style-type: none">■ Deep "V" Marine Grade Aluminum Hull■ Heavy Duty Transom Knee■ Non - Skid Rubber Floor Panels■ Plastic External Transom Plate■ Aluminum Internal Transom Plate with Security Lip■ Aluminum Bow Eye■ 3-4 Aluminum Davit Lifting Points■ Deck Drain with Plug	<ul style="list-style-type: none">■ Orca(CSM) Five Layer Coated Fabric■ Push Push Plastic Non-Corrosive 2 Stage Inflation Valves■ Raised Single Rub Rail■ 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes■ 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes■ 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes■ Removable Rowing Seat■ Oarlock Bases	<ul style="list-style-type: none">■ Telescopic Oars with Aluminum Shaft■ Paddle Holders■ Hand Pump■ Maintenance Kit■ Owner's Manual■ 3 Layer Reinforced Seams■ Rubber Protector on Full Length of Keel

O P T I O N A L F E A T U R E S	<ul style="list-style-type: none">■ Bow Locker/ Seat■ Tube Chaps■ Boat Cover	<ul style="list-style-type: none">■ Chock Set■ Bow Step with Fold Down Stainless Steel cleat■ Lateral Fold Down Stainless Steel Cleat

Iamina

9.5AL SUPERLIGHT

Aluminum Tenders



SPECS

Overall Length	: 9'6" / 2.90m	Number of Chambers	: 3	Shaft Length	: 15" / 38.1cm
Overall Beam	: 5'6" / 1.68m	Person Capacity	: 5	RDC Design Category	: C
Inside Length	: 6'11" / 2.11m	Weight	: 95lb / 43kg		
Inside Beam	: 2'6" / 0.76m	Recommended HP	: 8hp / 6.0kw		
Tube Diameter	: 17" / 0.43m	Maximum HP	: 15hp / 11.2kw		

STANDARD FEATURES

- Deep "V" Marine Grade Aluminum Hull
 - Stringer System Welded Under Aluminum Deck
 - Heavy Duty Transom Knee
 - Non - Skid Rubber Floor Panels
 - Plastic External Transom Plate
 - Aluminum Internal Transom Plate with Security Lip
 - Aluminum Bow Eye
 - 3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
 - Deck Drain with Plug
 - Orca(CSM) Five Layer Coated Fabric
 - Raised Single Rub Rail
 - Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 - 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
 - 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes
 - 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes
- Removable Rowing Seat
 - Oarlock Bases
 - Telescopic Oars with Aluminum Shaft
 - Paddle Holders
 - Hand Pump
 - Maintenance Kit
 - Owner's Manual
 - 3 Layer Reinforced Seams
 - Rubber Protector on Full Length of Keel

OPTIONAL FEATURES

- Tube Chaps
 - Boat Cover
 - Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
 - Bow Locker/ Seat
 - Lateral Fold Down Stainless Steel Cleat



Iammina

10AL SUPERLIGHT

Aluminum Tenders



SPECIFICATIONS	Overall Length	: 10'6" / 3.19m	Number of Chambers	: 3	Shaft Length	: 15" / 38.1cm
	Overall Beam	: 5'6" / 1.68m	Person Capacity	: 5	RDC Design Category	: C
	Inside Length	: 7'6" / 2.30m	Weight	: 117lb / 53kg		
	Inside Beam	: 2'8" / 0.81m	Recommended HP	: 10hp / 7.5kw		
	Tube Diameter	: 17" / 0.43m	Maximum HP	: 20hp / 14.9kw		

STANDARD FEATURES	<ul style="list-style-type: none">■ Deep "V" Marine Grade Aluminum Hull■ Stringer System Welded Under Aluminum Deck■ Heavy Duty Transom Knee■ Non - Skid Rubber Floor Panels■ Plastic External Transom Plate■ Aluminum Internal Transom Plate with Security Lip■ Aluminum Bow Eye■ 3-4 Aluminum Davit Lifting Points	<ul style="list-style-type: none">■ Aluminum Transom Tie Down & Towing Rings■ Deck Drain with Plug■ Orca(CSM) Five Layer Coated Fabric■ Raised Single Rub Rail■ Push Push Plastic Non-Corrosive 2 Stage Inflation Valves■ 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes■ 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes■ 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes	<ul style="list-style-type: none">■ Removable Rowing Seat■ Oarlock Bases■ Telescopic Oars with Aluminum Shaft■ Paddle Holders■ Hand Pump■ Maintenance Kit■ Owner's Manual■ 3 Layer Reinforced Seams■ Rubber Protector on Full Length of Keel
-------------------	---	--	--

OPTIONAL FEATURES	<ul style="list-style-type: none">■ Tube Chaps■ Boat Cover■ Chock Set■ Bow Step with Fold Down Stainless Steel Cleat■ Lateral Fold Down Stainless Steel Cleat■ Removable Stern Seat	<ul style="list-style-type: none">■ Fiberglass Console■ One Person Jockey Seat■ Two Person Jockey Seat■ Stainless Steel Helm Unit■ Bow Locker/ Seat■ Bench Seat with Storage.
-------------------	--	--

lammina

11AL SUPERLIGHT

Aluminum Tenders



S P E C S	Overall Length	: 11'6" / 3.50m	Number of Chambers	: 3	Shaft Length	: 20" / 50.8cm
	Overall Beam	: 5'7" / 1.70m	Person Capacity	: 6	RDC Design Category	: C
	Inside Length	: 8'6" / 2.60m	Weight	: 172lb / 78kg		
	Inside Beam	: 2'8" / 0.81m	Recommended HP	: 20hp / 14.9kw		
	Tube Diameter	: 17" / 0.43m	Maximum HP	: 30hp / 22.4kw		

S T A N D A R D F E A T U R E S	<ul style="list-style-type: none">■ Deep "V" Marine Grade Aluminum Hull■ Stringer System Welded Under Aluminum Deck■ Heavy Duty Transom Knee■ Non - Skid Rubber Floor Panels■ Plastic External Transom Plate■ Aluminum Internal Transom Plate■ Aluminum Bow Eye■ 3-4 Aluminum Davit Lifting Points■ Aluminum Transom Tie Down & Towing Rings	<ul style="list-style-type: none">■ Aluminum Bow Tie Down & Towing Rings■ Deck Drain with Plug■ Orca(CSM) Five Layer Coated Fabric■ Raised Single Rub Rail■ Push Push Plastic Non-Corrosive 2 Stage Inflation Valves■ 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes■ 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes■ 2 Inside Stern Single Orca (CSM) Fabric Handles on Tube	<ul style="list-style-type: none">■ Removable Stern Seat■ Paddles with Aluminum Shaft■ Paddle Holders■ Hand Pump■ Maintenance Kit■ Owner's Manual■ 3 Layer Reinforced Seams■ Rubber Protector on Full Length of Keel

O P T I O N A L F E A T U R E S	<ul style="list-style-type: none">■ Tube Chaps■ Boat Cover■ Chock Set■ Bow Step with Fold Down Stainless Steel Cleat■ Lateral Fold Down Stainless Steel Cleat■ Removable Rowing Seat■ Fiberglass Console with Forward Seat	<ul style="list-style-type: none">■ Fiberglass Console■ Bench Seat with Storage■ One Person Jockey Seat■ Two Person Jockey Seat■ Stainless Steel Helm Unit■ Bow Locker/ Seat



lammina

12AL SUPERLIGHT

Aluminum Tenders



S P E C S	Overall Length	: 12' / 3.66m	Number of Chambers	: 3	Shaft Length	: 20" / 50.8cm
	Overall Beam	: 6'1" / 1.85m	Person Capacity	: 6	RDC Design Category	: C
	Inside Length	: 8'10" / 2.70m	Weight	: 198lb / 90kg		
	Inside Beam	: 2'11" / 0.89m	Recommended HP	: 25hp / 18.7kw		
	Tube Diameter	: 18" / 0.46m	Maximum HP	: 30hp / 22.4kw		

STANDARDS
FEATURES

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Heavy Duty Transom Knee
- Non - Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate
- Aluminum Bow Eye
- 3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings

- Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
- Orca(CSM) Five Layer Coated Fabric
- Raised Double Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 2 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Single Orca (CSM) Fabric Handles on Tubes

- Removable Stern Seat
- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

OPTIONAL
FEATURES

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat
- Fiberglass Console with Forward Seat

- Fiberglass Console
- Bench Seat with Storage
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit
- Bow Locker/ Seat

Iammina

13AL SUPERLIGHT

Aluminum Tenders



S P E C S	Overall Length	: 13' / 3.96m	Number of Chambers	: 3	Shaft Length	: 20" / 50.8cm
	Overall Beam	: 6'7" / 2.00m	Person Capacity	: 7	RDC Design Category	: C
	Inside Length	: 9'10" / 3.00m	Weight	: 220lb/100kg		
	Inside Beam	: 3'3" / 0.99m	Recommended HP	: 30hp / 22.4kw		
	Tube Diameter	: 18" / 0.46m	Maximum HP	: 40hp / 29.8kw		

STANDARDS
FEATURES

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
- Heavy Duty Transom Knee
- Non - Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate
- Aluminum Bow Eye
- 3-4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings

- Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
- Orca(CSM) Five Layer Coated Fabric
- Raised Double Rub Rail
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of Double Orca(CSM) Fabric Handles on Tubes
- 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes

- Paddles with Aluminum Shaft
- Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- 3 Layer Reinforced Seams
- Rubber Protector on Full Length of Keel

OPTIONAL
FEATURES

- Tube Chaps
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Fiberglass Console
- Fiberglass Console with Forward Seat

- Bench Seat with Storage
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit
- Bow Locker/ Seat



lammina

14AL SUPERLIGHT

Aluminum Tenders



SPECIFICATIONS	Overall Length	: 14' / 4.27m	Number of Chambers	: 4	Shaft Length	: 20" / 50.8cm
	Overall Beam	: 6'7" / 2.00m	Person Capacity	: 8	RDC Design Category	: C
	Inside Length	: 10'10" / 3.30m	Weight	: 246lb / 112kg		
	Inside Beam	: 3'3" / 0.99m	Recommended HP	: 40hp / 29.8kw		
	Tube Diameter	: 19" / 0.48m	Maximum HP	: 50hp / 37.3kw		

STANDARDS FEATURES	<ul style="list-style-type: none">■ Deep "V" Marine Grade Aluminum Hull■ Stringer System Welded Under Aluminum Deck■ Heavy Duty Transom Knee■ Non - Skid Rubber Floor Panels■ Plastic External Transom Plate■ Aluminum Internal Transom Plate■ Aluminum Bow Eye■ 3-4 Aluminum Davit Lifting Points■ Aluminum Transom Tie Down & Towing Rings	<ul style="list-style-type: none">■ Aluminum Bow Tie Down & Towing Rings■ Deck Drain with Plug■ Orca(CSM) Five Layer Coated Fabric■ Raised Double Rub Rail■ Push Push Plastic Non-Corrosive 2 Stage Inflation Valves■ 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes■ 2 Inside Bow Sets of Triple Orca(CSM) Fabric Handles on Tubes■ 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes	<ul style="list-style-type: none">■ Paddles with Aluminum Shaft■ Paddle Holders■ Hand Pump■ Maintenance Kit■ Owner's Manual■ 3 Layer Reinforced Seams■ Rubber Protector on Full Length of Keel
--------------------	--	--	--

OPTIONAL FEATURES	<ul style="list-style-type: none">■ Tube Chaps■ Boat Cover■ Chock Set■ Bow Step with Fold Down Stainless Steel Cleat■ Lateral Fold Down Stainless Steel Cleat■ Fiberglass Console■ Fiberglass Console with Forward Seat	<ul style="list-style-type: none">■ Bench Seat with Storage■ One Person Jockey Seat■ Two Person Jockey Seat■ Stainless Steel Helm Unit■ Bow Locker/ Seat
-------------------	---	--

lammina

15AL SUPERLIGHT

Aluminum Tenders



S P E C S	Overall Length	: 15' / 4.57m	Number of Chambers	: 5	Shaft Length	: 20" / 50.8cm
	Overall Beam	: 6'9" / 2.06m	Person Capacity	: 9	RDC Design Category	: C
	Inside Length	: 11'8" / 3.55m	Weight	: 326lb / 148kg		
	Inside Beam	: 3'4" / 1.03m	Recommended HP	: 50hp / 37.3kw		
	Tube Diameter	: 19" / 0.48m	Maximum HP	: 60hp / 44.8kw		

S T A N D A R D S F E A T U R E S	<ul style="list-style-type: none">■ Deep "V" Marine Grade Aluminum Hull■ Stringer System Welded Under Aluminum Deck■ Heavy Duty Transom Knee■ Non - Skid Rubber Floor Panels■ Plastic External Transom Plate■ Aluminum Internal Transom Plate■ Aluminum Bow Eye■ 3-4 Aluminum Davit Lifting Points■ Aluminum Transom Tie Down & Towing Rings	<ul style="list-style-type: none">■ Aluminum Bow Tie Down & Towing Rings■ Deck Drain with Plug■ Orca(CSM) Five Layer Coated Fabric■ Raised Double Rub Rail■ Push Push Plastic Non-Corrosive 2 Stage Inflation Valves■ 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes■ 2 Inside Bow Sets of Quadruple Orca(CSM) Fabric Handles on Tubes■ 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes	<ul style="list-style-type: none">■ Paddles with Aluminum Shaft■ Paddle Holders■ Hand Pump■ Maintenance Kit■ Owner's Manual■ 3 Layer Reinforced Seams■ Rubber Protector on Full Length of Keel
---	--	---	--

O P T I O N A L F E A T U R E S	<ul style="list-style-type: none">■ Tube Chaps■ Boat Cover■ Chock Set■ Bow Step with Fold Down Stainless Steel Cleat■ Lateral Fold Down Stainless Steel Cleat■ Fiberglass Console■ Fiberglass Console with Forward Seat	<ul style="list-style-type: none">■ Bench Seat with Storage■ One Person Jockey Seat■ Two Person Jockey Seat■ Stainless Steel Helm Unit■ Bow Locker/ Seat
--	---	--



lammina

16AL SUPERLIGHT

Aluminum Tenders



S P E C S

Overall Length	: 16' / 4.88m	Number of Chambers	: 5	Shaft Length	: 20" / 50.8cm
Overall Beam	: 7' / 2.14m	Person Capacity	: 10	RDC Design Category	: C
Inside Length	: 12'8" / 3.85m	Weight	: 409lb / 186kg		
Inside Beam	: 3'6" / 1.08m	Recommended HP	: 50hp / 37.3kw		
Tube Diameter	: 20" / 0.51m	Maximum HP	: 60hp / 44.8kw		

S T A N D A R D
F E A T U R E S

- Deep "V" Marine Grade Aluminum Hull
 - Stringer System Welded Under Aluminum Deck
 - Heavy Duty Transom Knee
 - Non - Skid Rubber Floor Panels
 - Plastic External Transom Plate
 - Aluminum Internal Transom Plate
 - Aluminum Bow Eye
 - 3-4 Aluminum Davit Lifting Points
 - Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings
 - Deck Drain with Plug
 - Orca(CSM) Five Layer Coated Fabric
 - Raised Double Rub Rail
 - Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 - 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
 - 2 Inside Bow Sets of Quadruple Orca(CSM) Fabric Handles on Tubes
 - 2 Inside Stern Sets of Triple Orca (CSM) Fabric Handles on Tubes
- Paddles with Aluminum Shaft
 - Paddle Holders
 - Hand Pump
 - Maintenance Kit
 - Owner's Manual
 - 3 Layer Reinforced Seams
 - Rubber Protector on Full Length of Keel

O P T I O N A L
F E A T U R E S

- Tube Chaps
 - Boat Cover
 - Chock Set
 - Bow Step with Fold Down Stainless Steel Cleat
 - Lateral Fold Down Stainless Steel Cleat
 - Fiberglass Console
 - Fiberglass Console with Forward Seat
- Bench Seat with Storage
 - One Person Jockey Seat
 - Two Person Jockey Seat
 - Stainless Steel Helm Unit
 - Bow Locker/ Seat

