

## Profile

## A 15

**SUPERLIGHT** 

## Professional Aluminum Boats



	Overal Length	:	15′/ 4.57m	Number of Chambers	: 5	5	Maximum HP	:60hp / 44.8kw
S	Overal Beam	:	6'9"/ 2.06m	Person Capacity	: 9	9	Shaft Length	:20"/50.8cm
ш	Inside Length	:	11′8″/3.55m	Weight	: 3	383lb/174kg	RDC Design Category	:с
S P	Inside Beam	:	3′4″/ 1.03m	Weight with Bow Locker	: 4	401lb/182kg		
	Tube Diameter	:	19"/ 0.48m	Recommended HP	: 5	50hp /37.3kw		

- Deep "V" Marine Grade Aluminum Hull
- Stringer System Welded Under Aluminum Deck
  Life Line Around Tube

ΔS ωш

ЧĽ

z⊢

 $\triangleleft \triangleleft$ 

⊢ш

ഗഥ

л г

∢ш

Zĸ

0⊃

- 4

ு ய

Ош

- Non Skid(CSM) Coated Fabric on Tube's Surface
- Pressure Relief Valves
- Drain Scuppers

Tube Chaps

Boat Cover

Chock Set

- Heavy Duty Transom Knee Non Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate

- Aluminum Bow Eye 4 Aluminum Davit Lifting Points Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
- Heavy Duty 1670 Decitex Orca(CSM) Five Layer Coated Fabric 3 Layer Reinforced Seams Double Solid Rub Rails Rubber Protector on Full L
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
- Paddles with Aluminum Shaft Paddle Holders
- Hand Pump
- Maintenance Kit
- Owner's Manual
- Rubber Protector on Full Length of Keel

- Fiberglass Console
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Unit
- Aluminum Console
- Aluminum Lean On

Removable Rowing Seat Fiberglass Console with Forward Seat

Bow Step with Fold Down Stainless Steel Cleat

Lateral Fold Down Stainless Steel Cleat

Customized Aluminum Consoles & Seats Upon Request

Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank

Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings

