

Profile

A 13-S SUPERLIGHT Professional Shallow Water Aluminum Boats



	Overal Length	:	13'/ 3.96m	Number of Chambers	:	3	Maximum HP	: 40hp / 29.8kw
S P E C S	Overal Beam	:	6′5″/ 1.96m	Person Capacity	:	7	Shaft Length	:20″/50.8cm
	Inside Length	:	9'10"/ 3.00m	Weight	:	282lb/128kg	RDC Design Category	: С
	Inside Beam	:	3′3″/ 0.99m	Weight with Bow Locker	:	297lb/ 135kg		
	Tube Diameter	:	18"/ 0.46m	Recommended HP	:	30hp /22.4kw		

- Marine Grade Aluminum Hull Shallow Water Version
 Stringer System Welded Under Aluminum Deck
- Life Line Around Tube
- Non Skid(CSM) Coated Fabric on Tube's Surface
- Pressure Relief Valves

Tube Chaps

Boat Cover

Chock Set

Drain Scuppers

ΔS счш

ЧЧ

z⊢

A A

⊢ш

sΨ

<u>ہ ب</u>

ЧШ

Zœ

o⊃

⊢ ፈ

ு ய

Оц

· —

- Heavy Duty Transom Knee Non Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate

- Aluminum Bow Eye
 4 Aluminum Davit Lifting Points
 Aluminum Transom Tie Down & Towing Rings
- Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
- Heavy Duty 1670 Decitex Orca(CSM) Five Layer Coated Fabric Jayer Reinforced Seams
- Double Solid Rub Rails
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
- Fiberglass Console
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Uni
- Aluminum Console
- Aluminum Lean On

Fiberglass Console with Forward Seat Customized Aluminum Consoles & Seats Upon Request

Bow Step with Fold Down Stainless Steel Cleat

Lateral Fold Down Stainless Steel Cleat

Removable Rowing Seat



- Paddle Holders Hand Pump
- Maintenance Kit
- Owner's Manual

Paddles with Aluminum Shaft

Rubber Protector on Full Length of Keel

Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank

Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings