

Profile

A 14-S SUPERLIGHT

Professional Shallow Water Aluminum Boats



S P E C S	Overall Length	: 14' / 4.27m	Number of Chambers	: 4	Maximum HP	: 50hp / 37.3kw
	Overall Beam	: 6'5" / 1.96m	Person Capacity	: 8	Shaft Length	: 20" / 50.8cm
	Inside Length	: 10'10" / 3.30m	Weight	: 317lb / 144kg	RDC Design Category : C	
	Inside Beam	: 3'3" / 0.99m	Weight with Bow Locker : 335lb / 152kg			
	Tube Diameter	: 19" / 0.48m	Recommended HP : 40hp / 29.8kw			

S T A N D A R D F E A T U R E S	<ul style="list-style-type: none">Marine Grade Aluminum Hull - Shallow Water VersionStringer System Welded Under Aluminum DeckLife Line Around TubeNon - Skid(CSM) Coated Fabric on Tube's SurfacePressure Relief ValvesDrain ScuppersHeavy Duty Transom KneeNon - Skid Rubber Floor PanelsPlastic External Transom PlateAluminum Internal Transom Plate			<ul style="list-style-type: none">Aluminum Bow Eye4 Aluminum Davit Lifting PointsAluminum Transom Tie Down & Towing RingsAluminum Bow Tie Down & Towing RingsDeck Drain with PlugHeavy Duty 1670 Decitex Orca(CSM) Five Layer Coated FabricDouble Solid Rub RailsPush Push Plastic Non-Corrosive 2 Stage Inflation Valves1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes		
				<ul style="list-style-type: none">Paddles with Aluminum ShaftPaddle HoldersHand PumpMaintenance KitOwner's Manual3 Layer Reinforced SeamsRubber Protector on Full Length of Keel		

O P T I O N A L F E A T U R E S	<ul style="list-style-type: none">Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel TankPortable 6 Gal Fuel Tank Installed in Bow Locker with FittingsTube ChapsBoat CoverChock SetBow Step with Fold Down Stainless Steel CleatLateral Fold Down Stainless Steel CleatRemovable Rowing SeatFiberglass Console with Forward SeatCustomized Aluminum Consoles & Seats Upon Request			<ul style="list-style-type: none">Fiberglass ConsoleOne Person Jockey SeatTwo Person Jockey SeatStainless Steel Helm UniAluminum ConsoleAluminum Lean On		