

## Profile

## A 16-S SUPERLIGHT Professional Shallow Water **Aluminum Boats**



	Overal Length	:	16'/ 4.88m	Number of Chambers	: 5	Maximum HP	: 60hp/44.8kw
S	Overal Beam	:	7′/ 2.14m	Person Capacity	: 10	Shaft Length	:20″/50.8cm
ш	Inside Length	:	13'2"/4.01m	Weight	: 480lb/218kg	RDC Design Category	: С
SP	Inside Beam	:	3′6″/ 1.08m	Weight with Bow Locker	: 500lb/ 227kg		
	Tube Diameter	:	21″/ 0.53m	Recommended HP	: 50hp /37.3kw		

- Marine Grade Aluminum Hull Shallow Water Version
- Stringer System Welded Under Aluminum Deck
- Life Line Around Tube Non Skid(CSM) Coated Fabric on Tube's Surface
- Pressure Relief Valves
- Drain Scuppers

Tube Chaps

Boat Cover

Chock Set

Heavy Duty Transom Knee

ΩS പ ന

ЧЧ

 $\Box \supset$ 

zμ

×٩

⊢ш

SΨ

<u>ہ ר</u>

⊲ ш

ZĽ

0⊃

⊢∢

ு ய

Оц

- Non - Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate

- Aluminum Bow Eye
- 4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
  Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
- Heavy Duty 1670 Decitex Orca(CSM) Five Layer Coated Fabric
  - Double Solid Rub Rails
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves 1 Front & 5 Side Orca(CSM) Fabric Handles on Tubes
- Fiberglass Console
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Uni
- Aluminum Console
- Aluminum Lean On

- Paddle Holders
- Hand Pump
- Maintenance Kit Owner's Manual
- 3 Layer Reinforced Seams

Paddles with Aluminum Shaft

Rubber Protector on Full Length of Keel

Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank

Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings

Bow Step with Fold Down Stainless Steel Cleat

Customized Aluminum Consoles & Seats Upon Request

Lateral Fold Down Stainless Steel Cleat

Fiberglass Console with Forward Seat

Removable Rowing Seat