

## Profile

## A 11-S SUPERLIGHT Professional Shallow Water **Aluminum Boats**



	Overal Length	:	11′6″/ 3.50m	Number of Chambers	: 3	Maximum HP	: 30hp / 22.4kw
S P E C S	Overal Beam	:	5′7″/ 1.70m	Person Capacity	: 6	Shaft Length	:15″/38.1cm
	Inside Length	:	8'6"/ 2.60m	Weight	: 227lb / 103kg	RDC Design Category	: С
	Inside Beam	:	2′8″/ 0.81m	Weight with Bow Locker :	242lb/ 110kg		
	Tube Diameter	:	17"/ 0.43m	Recommended HP	: 20hp /14.9kw		

- Marine Grade Aluminum Hull Shallow Water Version
- Stringer System Welded Under Aluminum Deck
- Life Line Áround Tube Non Skid(CSM) Coated Fabric on Tube's Surface
- Pressure Relief Valves
- Drain Scuppers

ND сυ

ЧЧ

z⊢

 $\triangleleft \triangleleft$ 

μш

ωщ

<u>ہ ר</u>

∢ш

ZĽ

0⊃

ΓA

ு ய

Оц

- Heavy Duty Transom Knee
- Non - Skid Rubber Floor Panels
- Plastic External Transom Plate
- Aluminum Internal Transom Plate

- Aluminum Bow Eye
- 4 Aluminum Davit Lifting Points
- Aluminum Transom Tie Down & Towing Rings
  Aluminum Bow Tie Down & Towing Rings
- Deck Drain with Plug
- Heavy Duty 1670 Decitex Orca(CSM) Five Layer Coated Fabric
  - Double Solid Rub Rails
- Push Push Plastic Non-Corrosive 2 Stage Inflation Valves 1 Front & 4 Side Orca(CSM) Fabric Handles on Tubes
- Rubber Protector on Full Length of Keel

3 Layer Reinforced Seams

Paddles with Aluminum Shaft

Paddle Holders

Maintenance Kit

Hand Pump

Owner's Manual

- Bow Locker Storage with Vent to Fit a 6 Gal Portable Fuel Tank
- Portable 6 Gal Fuel Tank Installed in Bow Locker with Fittings
- **Tube Chaps**
- **Boat Cover**
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat
- Fiberglass Console with Forward Seat
- Customized Aluminum Consoles & Seats Upon Request



- Fiberglass Console
- One Person Jockey Seat
- Two Person Jockey Seat
- Stainless Steel Helm Uni
- Aluminum Console
- Aluminum Lean On