



STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Lifting Points
- Non-Skid Orca (CSM) Fabric On Top of Tube
- SEADEK® EVA FOAM NON-SKID FLOOR
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Bow Locker/Seat with Vent & Storage with Capacity to Fit a 6-Gal Portable Fuel Tank
 - Portable 6-Gal Fuel Tank Installed With Fittings" Bow Locker
 - Aluminum or Fiberglass Console With Plexiglass Windshield & Grab Rail
 - Fiberglass or Aluminum Jockey Consoles
 - Customized Aluminum Console and Seats
 - Aluminum Jockey Seat
 - Leaning Bolster
- Mechanical Steering System
 - Hydraulic Steering System
 - Standard Rigging From Factory
 - SS LED Navigation Light
 - All Around LED Anchor Light
 - Automatic Bilge Pump
 - Master Switch
 - Fuel/Water Separator & Canister
 - Sunbrella Fabric Boat Cover
 - Chock Set
 - Lifting Harness
 - Electronics Upon Request
 - Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	11' 6"	3.5 M
OVERALL BEAM	5' 7"	1.7 M
INSIDE LENGTH	8' 6"	2.6 M
INSIDE BEAM	2' 8"	0.81 M
TUBE DIAMETER	17"	0.43 M
NUMBER OF CHAMBERS	3	3
PERSON CAPACITY	6	6
WEIGHT	212 LBS	96 KG
WEIGHT WITH BOW LOCKER	229 LBS	104 KG
RECOMMENDED HP	20 HP	14.9 KW
MAXIMUM HP	30 HP	22.4 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	17°	17°
ALUMINUM HULL THICKNESS	0.125 in	3.18 MM
ALUMINUM TRANSOM THICKNESS	0.190 in	4.78 MM



STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Lifting Points
- Non-Skid Orca (CSM) Fabric On Top of Tube
- SEADEK® EVA FOAM NON-SKID FLOOR
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Bow Locker/Seat with Vent & Storage with Capacity to Fit a 6-Gal Portable Fuel Tank
 - Portable 6-Gal Fuel Tank Installed With Fittings" Bow Locker
 - Aluminum or Fiberglass Console With Plexiglass Windshield & Grab Rail
 - Fiberglass or Aluminum Jockey Consoles
 - Customized Aluminum Console and Seats
 - Aluminum Jockey Seat
 - Leaning Bolster
- Mechanical Steering System
 - Hydraulic Steering System
 - Standard Rigging From Factory
 - SS LED Navigation Light
 - All Around LED Anchor Light
 - Automatic Bilge Pump
 - Master Switch
 - Fuel/Water Separator & Canister
 - Sunbrella Fabric Boat Cover
 - Chock Set
 - Lifting Harness
 - Electronics Upon Request
 - Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	12'	3.66 M
OVERALL BEAM	6' 1"	1.85 M
INSIDE LENGTH	8' 10"	2.7 M
INSIDE BEAM	2' 11"	0.89 M
TUBE DIAMETER	18"	0.46 M
NUMBER OF CHAMBERS	3	3
PERSON CAPACITY	6	6
WEIGHT	231 LBS	105 KG
WEIGHT WITH BOW LOCKER	250 LBS	113 KG
RECOMMENDED HP	25 HP	18.7 KW
MAXIMUM HP	30 HP	22.4 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	19°	19°
ALUMINUM HULL THICKNESS	0.125 in	3.18 MM
ALUMINUM TRANSOM THICKNESS	0.190 in	4.78 MM

STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Lifting Points
- Non-Skid Orca (CSM) Fabric On Top of Tube
- SEADEK® EVA FOAM NON-SKID FLOOR
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Bow Locker/Seat with Vent & Storage with Capacity to Fit a 6-Gal Portable Fuel Tank
- Portable 6-Gal Fuel Tank Installed With Fittings" Bow Locker
- Aluminum or Fiberglass Console With Plexiglass Windshield & Grab Rail
- Fiberglass or Aluminum Jockey Consoles
- Customized Aluminum Console and Seats
- Aluminum Jockey Seat
- Leaning Bolster
- Mechanical Steering System
- Hydraulic Steering System
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump
- Master Switch
- Fuel/Water Separator & Canister
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	13'	3.96 M
OVERALL BEAM	6' 7"	2 M
INSIDE LENGTH	9' 10"	3 M
INSIDE BEAM	3' 3"	0.99 M
TUBE DIAMETER	18"	0.46 M
NUMBER OF CHAMBERS	3	3
PERSON CAPACITY	7	7
WEIGHT	278 LBS	126 KG
WEIGHT WITH BOW LOCKER	311 LBS	141 KG
RECOMMENDED HP	30 HP	22.4 KW
MAXIMUM HP	40 HP	29.8 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	18°	18°
ALUMINUM HULL THICKNESS	0.125 in	3.18 MM
ALUMINUM TRANSOM THICKNESS	0.190 in	4.78 MM

STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Lifting Points
- Non-Skid Orca (CSM) Fabric On Top of Tube
- SEADEK® EVA FOAM NON-SKID FLOOR
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Bow Locker/Seat with Vent & Storage with Capacity to Fit a 6-Gal Portable Fuel Tank
 - Portable 6-Gal Fuel Tank Installed With Fittings" Bow Locker
 - Aluminum or Fiberglass Console With Plexiglass Windshield & Grab Rail
 - Fiberglass or Aluminum Jockey Consoles
 - Customized Aluminum Console and Seats
 - Aluminum Jockey Seat
 - Leaning Bolster
- Mechanical Steering System
 - Hydraulic Steering System
 - Standard Rigging From Factory
 - SS LED Navigation Light
 - All Around LED Anchor Light
 - Automatic Bilge Pump
 - Master Switch
 - Fuel/Water Separator & Canister
 - Sunbrella Fabric Boat Cover
 - Chock Set
 - Lifting Harness
 - Electronics Upon Request
 - Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	14'	4.27 M
OVERALL BEAM	6' 7"	2 M
INSIDE LENGTH	10' 10"	3.3 M
INSIDE BEAM	3' 3"	0.99 M
TUBE DIAMETER	19"	0.48 M
NUMBER OF CHAMBERS	4	4
PERSON CAPACITY	8	8
WEIGHT	297 LBS	134 KG
WEIGHT WITH BOW LOCKER	312 LBS	142 KG
RECOMMENDED HP	40 HP	29.8 KW
MAXIMUM HP	50 HP	37 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	18°	18°
ALUMINUM HULL THICKNESS	0.125 in	3.18 MM
ALUMINUM TRANSOM THICKNESS	0.190 in	4.78 MM

STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Lifting Points
- Non-Skid Orca (CSM) Fabric On Top of Tube
- SEADEK® EVA FOAM NON-SKID FLOOR
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Hand Pump
- Maintenance Kit
- Owner's Manual



OPTIONAL FEATURES

- Bow Locker/Seat with Vent & Storage with Capacity to Fit a 6-Gal Portable Fuel Tank
- Portable 6-Gal Fuel Tank Installed With Fittings" Bow Locker
- Integrated Aluminum Fuel Tank
- Aluminum or Fiberglass Console With Plexiglass Windshield & Grab Rail
- Fiberglass or Aluminum Jockey Consoles
- Customized Aluminum Console and Seats
- Aluminum Jockey Seat
- Leaning Bolster
- Mechanical Steering System
- Hydraulic Steering System
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump
- Master Switch
- Fuel/Water Separator & Canister
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	15'	4.57 M
OVERALL BEAM	6' 9"	2.06 M
INSIDE LENGTH	11' 8"	3.55 M
INSIDE BEAM	3' 4"	1.03 M
TUBE DIAMETER	19"	0.48 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	9	9
WEIGHT	392 LBS	178 KG
WEIGHT WITH BOW LOCKER	421 LBS	191 KG
RECOMMENDED HP	50 HP	37 KW
MAXIMUM HP	60 HP	44.8 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	18°	18°
ALUMINUM HULL THICKNESS	0.190 in	4.78 MM
ALUMINUM TRANSOM THICKNESS	0.190 in	4.78 MM

STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Lifting Points
- Non-Skid Orca (CSM) Fabric On Top of Tube
- SEADEK® EVA FOAM NON-SKID FLOOR
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Hand Pump
- Maintenance Kit
- Owner's Manual

OPTIONAL FEATURES

- Bow Locker/Seat with Vent & Storage with Capacity to Fit a 6-Gal Portable Fuel Tank
 - Portable 6-Gal Fuel Tank Installed With Fittings" Bow Locker
 - Integrated Aluminum Fuel Tank
 - Aluminum or Fiberglass Console With Plexiglass Windshield & Grab Rail
 - Fiberglass or Aluminum Jockey Consoles
 - Customized Aluminum Console and Seats
 - Aluminum Jockey Seat
 - Leaning Bolster
- Mechanical Steering System
 - Hydraulic Steering System
 - Standard Rigging From Factory
 - SS LED Navigation Light
 - All Around LED Anchor Light
 - Automatic Bilge Pump
 - Master Switch
 - Fuel/Water Separator & Canister
 - Sunbrella Fabric Boat Cover
 - Chock Set
 - Lifting Harness
 - Electronics Upon Request
 - Color Boat Customization



SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	16'	4.88 M
OVERALL BEAM	7'	2.14 M
INSIDE LENGTH	13' 2"	3.85 M
INSIDE BEAM	3' 6"	1.08 M
TUBE DIAMETER	21"	0.53 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	10	10
WEIGHT	458 LBS	208 KG
WEIGHT WITH BOW LOCKER	479 LBS	217 KG
RECOMMENDED HP	50 HP	37 KW
MAXIMUM HP	70 HP	52.2 KW
SHAFT LENGTH	20"	50.8 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	18°	18°
ALUMINUM HULL THICKNESS	0.190 in	4.78 MM
ALUMINUM TRANSOM THICKNESS	0.190 in	4.78 MM



STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Lifting Points
- Non-Skid Orca (CSM) Fabric On Top of Tube
- SEADEK® EVA FOAM NON-SKID FLOOR
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Coated Fabric
- Lifeline Around Tube
- Hydraulic Steering System
- SS LED Navigation Light
- All Around Anchor Light
- Standard Rigging From Factory
- Aluminum Console with Plexiglass Windshield & Grab Rail
- Leaning Bolster
- Integrated Aluminum Fuel Tank
- Fuel Sending Unit
- Bow Locker
- Hand Pump
- Maintenance Kit



OPTIONAL FEATURES

- Fiberglass or Aluminum Jockey Consoles
- Customized Aluminum Consoles & Seats
- Aluminum Jockey Seat
- Sunbrella Fabric Boat Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization

SPECIFICATION	IMPERIAL	METRIC
OVERALL LENGTH	18'	5.49 M
OVERALL BEAM	7' 11"	2.40 M
INSIDE LENGTH	14' 8"	4.47 M
INSIDE BEAM	4' 3"	1.30 M
TUBE DIAMETER	21"	0.53 M
NUMBER OF CHAMBERS	5	5
PERSON CAPACITY	15	15
WEIGHT	859 LBS	390 KG
RECOMMENDED HP	90 HP	67 KW
MAXIMUM HP	115 HP	85.8 KW
SHAFT LENGTH	25"	63.5 CM
RDC DESIGN CATEGORY	C	C
DEADRISE	22°	22°
ALUMINUM HULL THICKNESS	0.190 in	4.78 MM
ALUMINUM TRANSOM THICKNESS	0.250 in	6.35 MM
FUEL BUILT-IN TANK	32 GAL	120 LT

* EPA built-in fuel tank 7% capacity reduction approx.