11 VSX Lightweight fiberglass Console Tenders



: 11'4"/ 3.45m Overal Length Number of Chambers Overal Beam 5' 9"/ 1.77m Person Capacity : 4 : 315lb / 143kg Inside Length 8'1"/ 2.47m Weight Inside Beam 2' 8"/ 0.81m Recommended HP : 30hp / 22.4 kw Tube Diameter : 18"/ 0.46m Maximum HP : 40hp / 29.8 kw

 ∇ 出足 K W Q D $Z \vdash$ AA LШ ∞ \Box

S

(II)

S

- Removable Lateral Seat
 Bow Locker Storage to Fit a 6 Gal. Portable Fuel Tank
 Foldable Console
 Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Diamond Shape Non-skid Deck
 Plastic External Transom Plate
 Aluminum Internal Transom Plate
 1 Front & 2Side Orca (CSM) Fabric Handles on Tubes
 1 Port Inside Transom Orca (CSM) Fabric Handles on Tubes
 2 Inside Bow Sets of Double Orca (CSM) Fabric Handles on Tubes
 Raised Single Solid Rub Rail
 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
 Orca (CSM) Five Layer Coated Fabric
 Hand Pump

- Hand Pump Maintenan ce Kit

- Owner's Manual
 Marine Cell Foam Uphols tery
 Fiberglass Console with Cup Holder & SS Grab Handle
 Integrated Stern Seat with Storage
 2 Deck Drain & HullDrain with Plug

- Bow Locker/Seat with Vent Bow Hatch Cushion

- Bow Hatch Cushion
 LEDNavigation Side Lights
 360° LEDWhite Navigation Pole
 4 Stainless Steel Davit Lfting Points
 Stainless Steel Bow Eye
 Stainless Steel Tow Rings & Tie Downs
 Stainless Steel Gas Springs
 Luxury LookPannel
 2 Waterproof Rocker Switches with Circuit Brakers
 Battery Box

Shaft Length

RDCDesign Category · C

- Battery Switch
 Automatic Bilge Pump 500 GPH
 Mechanical Steering System
 Stainless Steel Steering Wheel
 Complete Tin Wiring & Heat Shrink Sealed Terminals
 3 Layer Reinforced Seams

: 20"/ 50.8cm

 $\mathbb{Z} \simeq$ БΕ ОН

- Portable 6 Gal. Fuel Tank Installed in Bow Locker with Fittings
- Stainless Steel Light Arch
- Bimini Top with Stainless Steel Tubing
- Chock Set
- Boat Cover
- Console Cover
- Lifting Harness

- Teak Floor
- CD/Radio System
- Compass
- GPS
- VHFPackage

