## mares

## 12 VSX Lightweight fiberglass Console Tenders



S

S

 $_{\rm S}$ 出区 K W Q D  $Z \vdash$ AA ΗШ  $\Sigma$ 

 $\sim$ E

 $\mathbb{Z} \mathbb{Z}$ 

0

ДΞ ОН Overal Length : 12′/3.66m Number of Chambers : 3 Shaft Length : 20"/50.8cm Overal Beam Person Capacity : 5 RDC Design Category: C : 6'/ 1.82m Inside Length : 8′9"/2.67m Weight : 337lb / 153kg Inside Beam : 2'9"/ 0.84m Recommended HP : 30hp / 22.4kw : 40hp / 29.8kw Tube Diameter : 18"/ 0.46m Maximum HP

- Hand Laid Fiberglass Deep "V" Hull
  Stringer System Laminated into Hull
  Diamond Shape Non-skid Deck
  Plastic External Transom Plate
  Aluminum Internal Transom Plate
  1 Front & 2 Side Orea (CSM) Fabric Handles on Tubes
  1 Port Inside Transom Orea (CSM) Fabric Handles on Tubes
  2 Inside Bow Sets of Double Orea (CSM) Fabric Handles on Tubes
  Raised Single Solid Rub Rail
  Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
  Orea (CSM) Five Layer Coated Fabric
  Hand Pump

- Hand Pump
  Maintenance Kit
  Owner's Manual
  Marine Cell Foam Upholstery
  Fiberglass Console with Cup Holder & SS Grab Handle
- Integrated Stern Seat with Storage 2 Deck Drain & Hull Drain with Plug Bow Locker/Seat Bow Hatch Cushion LED Navigation Side Lights

- 360° LED White Navigation Pole 4 Stainless Steel Davit Lifting Points Stainless Steel Bow Eye Stainless Steel Tow Rings & Tie Downs Stainless Steel Gas Springs

- Stainless Steel Gas Springs
   Luxury Look Pannel
   2 Waterproof Rocker Switches with Circuit Brakers
   Battery Box
   Battery Switch

- Automatic Bilge Pump 500 GPH Mechanical Steering System Stainless Steel Steering Wheel Complete Tin Wiring & Heat Shrink Sealed Terminals 3 Layer Reinforced Seams

- Stainless Steel Light Arch
- Bimini Top with Stainless Steel Tubing
- Chock Set
- Boat Cover
- Console Cover
- Lifting Harness

- Teak Floor
- CD/Radio System
- Compass
- GPS
- VHF Package

