



S P E C S	Overall Length	: 14' / 4.27m	Number of Chambers	: 4 + 1	Shaft Length	: 20" / 50.8cm
	Overall Beam	: 6'4" / 1.94m	Person Capacity	: 8	RDC Design Category	: C
	Inside Length	: 10'10" / 3.30m	Weight	: 348lb / 158kg		
	Inside Beam	: 3'1" / 0.94m	Recommended HP	: 40hp / 29.8kw		
	Tube Diameter	: 19" / 0.48m	Maximum HP	: 50hp / 37.3kw		

STANDARD FEATURES

- Hand Laid Fiberglass Deep “V” Hull
- Stringer System Laminated into Hull
- Bow Locker/ Seat with Vent
- Bow Locker Storage to Fit a 6 Gal. Portable Fuel Tank
- Diamond Shape Non - Skid Deck
- Plastic External Transom Plate
- Aluminum Internal Transom Plate
- Orca (CSM) Five Layer Coated Fabric
- 4 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Raised Double Rub Rail
- Stainless Steel Bow Eye

- 4 Stainless Steel Davit Lifting Points
- Stainless Steel Towing Rings & Tie Downs
- Deck Condensation Plug
- Deck Drain with Plug
- 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of 3 Orca (CSM) Fabric Handles on Tubes
- 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams
- Paddle with Aluminum Shaft
- Paddle Holders

- Hand Pump
- Maintenance Kit
- Owner's Manual
- Additional Air Retaining Chamber Under the Floor
- Hidden Channel for Fuel Fittings with SS Starburst

OPTIONAL
FEATURES

- Portable 6 Gal. Fuel Tank Installed in Bow Locker with Fittings
- Bow Hatch Cushion
- Boat Cover
- Chock Set
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat

- Bimini Top
- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit