

navigo

17VS

Open FiberglassTenders



	Overal Length	:	17′/ 5.18m	Number of Chambers	:	5	Shaft Length	:20″/50.8cm
S P E C S	Overal Beam	:	8´1"/ 2.46m	Person Capacity	:	15	RDC Design Category	: C
	Inside Length	:	13´1"/ 4.00m	Weight	:	772lb / 350kg		
	Inside Beam	:	4′4″/ 1.33m	Recommended HP	:	75hp / 56kw		
	Tube Diameter	:	20″/ 0.50m	Maximum HP	:	90hp / 67kw		

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
- Stringer System Laminated into Hull Bow Locker/ Seat
- Diamond Shape Non - Skid Deck

ND

പ

ЧЧ

z⊢

 $\triangleleft \triangleleft$

μш

νц

<u>ہ ר</u>

∢ш

Zĸ

0⊃

⊢∢

പപ

Оц

- Plastic External Transom Plate

- Aluminum Internal Transom Plate Orca (CSM) Five Layer Coated Fabric 4 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves

Bow Step with Fold Down Stainless Steel Cleat

Lateral Fold Down Stainless Steel Cleat

- Raised Double Solid Rub Rail Stainless Steel Bow Eye

Bow Hatch Cushion

Removable Rowing Seat

Fuel Tank

Boat Cover

Chock Set

- 4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 2 Deck Drains with Plug
 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes
- 2 Inside Bow Sets of 3 Orca (CSM) Fabric Handles on Tubes 2 Inside Stern of 3 Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams Paddle with Aluminum Shaft
- Paddle Holders
- Hand Pump

Bimini Top

Maintenance KitOwner's Manual

- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit