

navigo

19VS

Open FiberglassTenders



	Overal Length	:	19′/ 5.79m	Number of Chambers	:	5	Shaft Length	:25″/63.5cm
S P E C S	Overal Beam	:	8´4"/ 2.53m	Person Capacity	:	15	RDC Design Category	: C
	Inside Length	:	15´2″/ 4.62m	Weight	:	1157lb / 526kg		
	Inside Beam	:	4´1"/ 1.25m	Recommended HP	:	115hp / 85.8kw		
	Tube Diameter	:	22"/ 0.56m	Maximum HP	:	150hp / 111.9kw		

- Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
- Stringer System Laminated into Hull Bow Locker/ Seat

ΩS

പ

ЧЧ

z⊢

 $\triangleleft \triangleleft$

μш

νц

<u>ہ ר</u>

∢ш

ZĽ

0⊃

ΓA

പപ

Оц

- ----

- Diamond Shape Non - Skid Deck
- Plastic External Transom Plate
- Aluminum Internal Transom Plate Orca (CSM) Five Layer Coated Fabric 4 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves
- Raised Double Solid Rub Rail Stainless Steel Bow Eye

Bow Step with Fold Down Stainless Steel Cleat

Lateral Fold Down Stainless Steel Cleat

Fuel Tank

Boat Cover

Chock Set

Bow Hatch Cushion

Removable Rowing Seat

- 4 Stainless Steel Davit Lifting Points
 Stainless Steel Towing Rings & Tie Downs
 Deck Condensation Plug

- 2 Deck Drains with Plug 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes 2 Inside Bow Sets of 2 Orca (CSM) Fabric Handles on Tubes 2 Inside Stern Double Orca (CSM) Fabric Handles on Tubes
 - 3 Layer Reinforced Seams
- Paddle with Aluminum Shaft Paddle Holders

- Hand Pump Maintenance Kit
 Owner's Manual
- Deck Storage

- Bimini Top
- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit

