A A

 \forall \vdash \sqcup

SН

Ош



Professional Fiberglass Boats



Overal Length	: 14′/ 4.27m	Number of Chambers	: 4+1	Shaft Length	: 20" / 50.8cm
Overal Beam	: 6'4"/ 1.94m	Person Capacity	: 8	RDC Design Category	: C
Inside Length	: 10′10″/ 3.30m	Weight	: 403lb / 183kg		
Inside Beam	: 3′1″/ 0.94m	Recommended HP	: 40hp / 29.8kw		
Tube Diameter	: 19"/ 0.48m	Maximum HP	: 50hp/37.3kw		

- Professional Grade Hand Laid Fiberglass Deep "V" Hull
 Stringer System Laminated into Hull
 Bow Locker/ Seat

- Diamond Shape Non Skid Deck
- Plastic External Transom Plate
- Aluminum Internal Transom Plate
- Heavy Duty 1670 Decitex Orca (CSM) Five Layer Coated Fabric Life Line Around Tube
- Non Skid (CSM) Coated Fabric on Tube's Surface
- Pressure Relief Valves

- 4 Push Push Plastic Non-Corrosive 2 Stage Inflation Valves Paddle Holders
- Double Solid Rub Rail Stainless Steel Bow Eye
- 4 Stainless Steel Davit Lifting Points
- Stainless Steel Towing Rings & Tie Downs
- **Deck Condensation Plug**
- Deck Drain with Plug

 1 Front & 4 Side Orca (CSM) Fabric Handles on Tubes
- 3 Layer Reinforced Seams
- Paddle with Aluminum Shaft

- Removable Stern Seat Hand Pump
- Maintenance Kit
- Owner's Manual
- Additional Air Retaining Chamber Under the Floor
- Drain Scuppers
 Rubber Protector on Full Length of Keel

- Bow Hatch Cushion
- Boat Cover
- Bow Step with Fold Down Stainless Steel Cleat
- Lateral Fold Down Stainless Steel Cleat
- Removable Rowing Seat

- Bimini Top
- Fiberglass Console
- Fiberglass Console with Forward Seat
- Bench Seat with Storage
- Two person Jockey Seat
- Stainless Steel Helm Unit

