

PROFILE



IAB



INVULNERABLE

PROFILE



Our company was founded on a commitment to quality that guides us to this day. We are the only company in the world that manufactures its boats exclusively in-house, overseeing every aspect from start to finish, meeting or exceeding certified industry benchmarks and the standards for most globally recognized organizations. We keep meticulous records so there are never any surprises. Our ever-evolving quality-control measures ensure we always live up to our promise to build the best boats in the world.



PROFILE F

PROFESSIONAL FIBERGLASS BOATS

PROFILE F 17



MILITARY GRADE ORCA (CSM) FABRIC | FIBERGLASS REINFORCED PROFESSIONAL GRADE HULL
UNSURPASSED PERFORMANCE | OPEN AND SPACIOUS DESIGN | DEEP V HULL

STANDARD FEATURES

- Bow Eye
- Double Solid Rub Rail
- Towing Rings
- 3-4 Stainless Steel Lifting Points (Except 21-28)
- Non-Skid Orca (CSM) Fabric On Top Of Tube
- Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Fabric
- Life Line Around Tube
- Bow Locker
- Pressure Relief Valves
- Open Version (14-17)
- Hydraulic Steering System (19-28)
- SS LED Navigation Light (19 - 28)
- All Around LED Anchor Light (19-28)
- Standard Rigging From Factory (19-28)
- Automatic Bilge Pump (19-28)
- Master Switch (19-28)
- Battery Charger (19-28 / Subject To Country Of Delivery)
- Fuel/Water Separator & Canister (19-28)
- Fuel Sending Unit (19-28)
- Fiberglass Console With Plexiglass Windshield & Grab Rail (19-28)
- Leaning Bolster (19-28)
- Integrated Aluminum Fuel Tank (19-28)
- Bow Step (19-28)
- 3 Stainless Steel Fold Down Cleats (19-28)
- Rubber Keel Protector (F 14 & F 15)
- Hand Pump
- Maintenance Kit
- Owner's Manual

OPTIONAL FEATURES

- Fiberglass Or Aluminum Jockey Consoles
- Fiberglass Consoles
- Leaning Bolsters
- Customized Aluminum Consoles And Seats
- Mechanical Steering System (14-17)
- SS LED Navigation Light (14-17)
- All Around LED Anchor Light (14-17)
- Standard Rigging From Factory (14-17)
- Bow Step With Stainless Steel Fold Down Cleat (14-17)
- Lateral Stainless Steel Fold Down Cleat (14-17)
- Portable Fuel Tank (14)
- Integrated Aluminum Fuel Tank (15-17)
- Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Bimini Top
- T-Top
- Light Arch
- Engine Guard
- Stern/Bow Towing Post
- Color Boat Customization
- Master Switch

7 MODELS FROM 14 TO 28 FEET	F 14	F 15	F 17	F 19	F 21	F 24	F 28
LENGTH	14' (4.27 M)	15' (4.57 M)	17' (5.18 M)	19' (5.79 M)	21'4" (6.50 M)	24' (7.31 M)	27' (8.23 M)
BEAM	6'4" (1.94 M)	6'6" (1.99 M)	8'1" (2.46 M)	8'4" (2.53 M)	8'10" (2.70 M)	9'3" (2.82 M)	10'1" (3.07 M)
INSIDE LENGTH	10'10" (3.3 M)	11'6" (3.5 M)	13'1" (4 M)	15'2" (4.62 M)	17'3" (5.25 M)	19'3" (5.87 M)	22'11" (6.99 M)
INSIDE BEAM	3' 1" (0.94 M)	3'2" (0.97 M)	4'4" (1.33 M)	4'1" (1.25 M)	4'9" (1.44 M)	5'4" (1.64 M)	6'4" (1.93 M)
TUBE DIAMETER	19" (0.48 M)	19" (0.48 M)	20" (0.50 M)	22" (0.56 M)	22" (0.56 M)	24" (0.61 M)	24" (0.61 M)
CAPACITY PERSONS	8	11	15	15	20	20	25
WEIGHT	403* LBS (183* KG)	484* LBS (220* KG)	772* LBS (350* KG)	1157 LBS (526 KG)	1642 LBS (745 KG)	1980 LBS (900 KG)	2853 LBS (1297 KG)
RECOMMENDED HP	40	60	75	115	150	150	250
MAXIMUM HP	50	75	90	150	225	250	500



PROFILE

PROFESSIONAL ALUMINUM BOATS

PROFILE A 12







MILITARY GRADE ORCA (CSM) FABRIC | ALUMINUM REINFORCED PROFESSIONAL GRADE HULL
DURABLE ENOUGH FOR ROCKY SHORES & CORAL REEFS | CUSTOM ACCESSORIES UPON REQUEST | DEEP V HULL

STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Lifting Points
- Non-Skid Orca (CSM) Fabric On Top Of Tube
- Seadeck® Eva Foam Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Fabric
- Life Line Around Tube
- Hydraulic Steering System (18)
- SS Led Navigation Light (18)
- All Around Led Anchor Light (18)
- Standard Rigging From Factory (18)
- Aluminum Console With Plexiglass Windshield & Grab Rail (18)
- Leaning Bolster (18)
- Integrated Aluminum Fuel Tank (18)
- Fuel Sending Unit (18)
- Bow Locker (18)
- Hand Pump
- Maintenance Kit
- Owner's Manual

OPTIONAL FEATURES

- Bow Locker
- Portable Fuel Tank Installed In Bow Locker
- Aluminum Console
- Fiberglass Or Aluminum Jockey Consoles
- Customized Aluminum Consoles And Seats
- Aluminum Jockey Seat
- Leaning Bolster
- Mechanical Steering System
- Hydraulic Steering System
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around Led Anchor Light
- Automatic Bilge Pump
- Master Switch
- Fuel/Water Separator & Canister
- Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- T-Top (A 18)
- Light Arch (A 18)
- Engine Guard (A 18)
- Stern / Bow Towing Post (A 18)
- Color Boat Customization

7 MODELS FROM 11 TO 18 FEET	A 11	A 12	A 13	A 14	A 15	A 16	A 18
							
LENGTH	11'6" (3.5 M)	12' (3.66 M)	13' (3.96 M)	14' (4.27 M)	15' (4.57 M)	16' (4.88 M)	18' (5.49 M)
BEAM	5'7" (1.7 M)	6'1" (1.85 M)	6'7" (2 M)	6'7" (2 M)	6'9" (2.06 M)	7' (2.14 M)	7'11" (2.40 M)
INSIDE LENGTH	8'6" (2.6 M)	8'10" (2.7 M)	9'10" (3 M)	10'10" (3.3 M)	11'8" (3.55 M)	13' 2" (3.85 M)	14'8" (4.47 M)
INSIDE BEAM	2'8" (0.81 M)	2'11" (0.89 M)	3'3" (0.99 M)	3'3" (0.99 M)	3'4" (1.03 M)	3'6" (1.08 M)	4'3" (1.30 M)
TUBE DIAMETER	17" (0.43 M)	17" (0.43 M)	18" (0.46 M)	19" (0.48 M)	19" (0.48 M)	21" (0.53 M)	21" (0.53 M)
CAPACITY PERSONS	6	6	7	8	9	10	15
WEIGHT	212 LBS (96 KG)	231 LBS (105 KG)	278 LBS (126 KG)	297 LBS (134 KG)	392 LBS (178 KG)	458 LBS (208 KG)	
WEIGHT WITH BOW LOCKER	229 LBS (104 KG)	250 LBS (113 KG)	311 LBS (141 KG)	312 LBS (142 KG)	421 LBS (191 KG)	479 LBS (217 KG)	859 LBS (390 KG)
RECOMMENDED HP	20	25	30	40	50	50	90
MAXIMUM HP	30	30	40	50	60	70	115
SHAFT LENGTH	20" (50.8 CM)	20" (50.8 CM)	20" (50.8 CM)	20" (50.8 CM)	20" (50.8 CM)	20" (50.8 CM)	25" (63.5 CM)



PROFESSIONAL ALUMINUM SHALLOW WATER BOATS

PROFILE A 16-S



MILITARY GRADE ORCA (CSM) FABRIC | ALUMINUM REINFORCED PROFESSIONAL GRADE HULL
DURABLE ENOUGH FOR ROCKY SHORES | SHALLOW WATER VERSION HULL | CUSTOM ACCESSORIES UPON REQUEST





STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Bow Eye
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rub Rail
- Tow Rings
- 3-4 Aluminum Lifting Points
- Non-Skid Orca (CSM) Fabric On Top Of Tube

- Seadeck® Eva Foam Non-Skid Floor
- 4 Layer Reinforced Seams
- Heavy Duty 1670 Decitex
- Orca (CSM) Fabric
- Life Line Around Tube
- Hand Pump
- Maintenance Kit
- Owner's Manual

OPTIONAL FEATURES

- Bow Locker
- Portable Fuel Tank Installed In Bow Locker
- Aluminum Console
- Fiberglass Or Aluminum Jockey Consoles
- Customized Aluminum Consoles And Seats
- Aluminum Jockey Seat
- Leaning Bolster
- Mechanical Steering System
- Hydraulic Steering System
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump
- Master Switch
- Fuel/Water Separator & Canister
- Cover
- Chock Set
- Lifting Harness
- Electronics Upon Request
- Color Boat Customization

5 MODELS FROM 11 TO 16 FEET	A 11-S	A 12-S	A 13-S	A 14-S	A 16-S
					
LENGTH	11'6" (3.5 M)	12' (3.66 M)	13' (3.96 M)	14' (4.27 M)	16' (4.88 M)
BEAM	5'7" (1.7 M)	5'11" (1.8 M)	6'5" (1.96 M)	6'5" (1.96 M)	7' (2.14 M)
INSIDE LENGTH	8'6" (2.6 M)	8'10" (2.7 M)	9'10" (3 M)	10'10" (3.3 M)	12'8" (3.85 M)
INSIDE BEAM	2'8" (0.81 M)	2'10" (0.86 M)	3'3" (0.99 M)	3'3" (0.99 M)	3'6" (1.08 M)
TUBE DIAMETER	17" (0.43 M)	17" (0.43 M)	18" (0.46 M)	19" (0.48 M)	21" (0.53 M)
CAPACITY PERSONS	6	6	7	8	10
WEIGHT	227 LBS (103 KG)	242 LBS (110 KG)	282 LBS (128 KG)	317 LBS (144 KG)	480 LBS (218 KG)
WEIGHT WITH BOW LOCKER	247 LBS (112 KG)	262 LBS (119 KG)	295 LBS (134 KG)	335 LBS (152 KG)	501 LBS (227 KG)
RECOMMENDED HP	20	25	30	40	50
MAXIMUM HP	30	30	40	50	60
SHAFT LENGTH	15" (38.1 CM)	15" (38.1 CM)	20" (50.8 CM)	20" (50.8 CM)	20" (50.8 CM)



PROFESSIONAL ALUMINUM CONSOLE BOATS

PROFILE A 21-XHD



OVERBUILT REINFORCED PROFESSIONAL GRADE HULL | MILITARY GRADE ORCA (CSM) FABRIC
CUSTOMIZABLE UPON REQUEST | LARGE CAPACITY FOR CREW AND EQUIPMENT | IDEAL FOR TOUGH OPERATIONS

STANDARD FEATURES

- Marine Grade Aluminum Hulls
- Hydraulic Steering System
- Bow Locker
- Leaning Bolster
- Bow Towing Post
- Aluminum Console With Plexiglass Windshield & Rail
- Integrated Aluminum Fuel Tank
- Standard Rigging From Factory
- SS LED Navigation Light
- All Around LED Anchor Light
- Automatic Bilge Pump
- Master Switch
- Fuel/Water Separator & Canister
- Fuel Sending Unit
- Reinforced Aluminum Bow Eye
- Reinforced Aluminum Tow Rings
- Drain Scuppers
- Pressure Relief Valves
- Solid Double Rubrail
- 4 Aluminum Davit Lifting Points
- Non-Skid Orca (CSM) Fabric On Top Of Tube
- Heavy Duty Non-Skid Rubber Floor Panels
- 4 Layer Reinforced Seams

- Heavy Duty 1670 Decitex Orca
- Orca (CSM) Fabric
- Life Line Around Tube
- Hand Pump
- Maintenance Kit
- Owner's Manual

OPTIONAL FEATURES

- Customized Aluminum Consoles And Seats
- Fiberglass Or Aluminum Jockey Consoles
- Aluminum Jockey Seats
- Bow Rider Seats
- Cover
- Lifting Harness
- Electronics Upon Requests
- T-Top
- Stern Towing Post
- Light Arch
- Engine Guard
- Color Boat Customization

2 MODELS • 21 AND 24	A 21-XHD	A 24-XHD
LENGTH	21' (6.4 M)	24'8" (7.52 M)
BEAM	9'1" (2.77 M)	9'2" (2.80 M)
INSIDE LENGTH	16'5" (5 M)	19'9" (6.02 M)
INSIDE BEAM	4'6" (1.37 M)	4'8" (1.42 M)
TUBE DIAMETER	22" (0.56 M)	24" (0.61 M)
CAPACITY PERSONS	17	20
WEIGHT	1580 LBS (717 KG)	1758 LBS (799 KG)
RECOMMENDED HP	150	150
MAXIMUM HP	200	250

SPECIFICATIONS

SPECIFICATIONS									PROFILE F								PROFILE A								PROFILE AS					PROFILE A-XHD	
									F 14	F 15	F 17	F 19	F 21	F 24	F 28	A 11	A 12	A 13	A 14	A 15	A 16	A 18	A 11-S	A 12-S	F 13-S	A 14-S	A 16-S	A 21	A 24		
LENGTH																															
OVERALL	ft/in	14'	15'	17'	19'	21' 4"	24'	27'	11'6"	12'	13'	14'	15'	16'	18'	11'6"	12'	13'	14'	16'	21'	24' 8"									
	m	4.27	4.57	5.18	5.79	6.50	7.31	8.23	3.5	3.66	3.96	4.27	4.57	4.88	5.49	3.5	3.66	3.96	4.27	4.88	6.4	7.52									
INSIDE	ft/in	10'10"	11'6"	13'1"	15'2"	17' 3"	19'3"	22' 11"	8'6"	8'10"	9'10"	10'10"	11'8"	13' 2"	14'8"	8'6"	8'10"	9'10"	10'10"	12' 8"	16' 5"	19' 9"									
	m	3.3	3.5	4	4.62	5.25	5.87	6.99	2.6	2.7	3	3.3	3.55	3.85	4.47	2.6	2.7	3	3.3	3.85	5	6.02									
BEAM																															
OVERALL	ft/in	6'4"	6'6"	8'1"	8'4"	8'10"	9'3"	10'11"	5'7"	6'1"	6'7"	6'7"	6'9"	7"	7'11"	5'7"	5'11"	6'5"	6'5"	7"	9'1"	9'2"									
	m	1.94	1.99	2.46	2.53	2.70	2.82	3.07	1.7	1.85	2	2	2.06	2.14	2.40	1.7	1.8	1.96	1.96	2.14	2.77	2.80									
INSIDE	ft/in	3' 1"	3'2"	4'4"	4'1"	4'9"	5'4"	6' 4"	2'8"	2'11"	3'3"	3'3"	3'4"	3'6"	4'3"	2'8"	2'10"	3'3"	3'3"	3'6"	4'6"	4' 8"									
	m	0.94	0.97	1.33	1.25	1.44	1.64	1.93	0.81	0.89	0.99	0.99	1.03	1.08	1.30	0.81	0.86	0.99	0.99	1.08	1.37	1.42									
AREA																															
INTERNAL AREA	sq.ft.	33.39	36.54	57.26	62.16	81.38	103.62	145.21	22.67	25.87	31.97	35.17	39.36	44.76	62.55	22.67	25	31.97	35.17	44.76	73.73	92.01									
	m2	3.10	3.40	5.32	5.78	7.56	9.63	13.49	2.11	2.40	2.97	3.27	3.66	4.16	5.81	2.11	2.32	2.97	3.27	4.16	6.85	8.55									
MAX TUBE DIAMETER																															
	ft/in	19"	19"	20"	22"	22"	24"	24"	17"	17"	18"	19"	19"	21"	21"	17"	17"	18"	19"	21"	22"	24"									
	m	0.48	0.48	0.50	0.56	0.56	0.61	0.61	0.43	0.43	0.46	0.48	0.48	0.53	0.53	0.43	0.43	0.46	0.48	0.53	0.56	0.61									
NUMBER OF CHAMBERS																															
		4+1	5	5	5	5	6	6	3	3	3	4	5	5	5	3	3	3	4	5	6	6									
CAPACITY																															
PERSONS		8	11	15	15	20	20	25	6	6	7	8	9	10	15	6	6	7	8	10	17	20									
PAYLOAD	lbs	2,347	2,557	2,965	3,999	4,100	4,526	5,035	1,644	2,032	2,092	2,392	2,608	2,600	3,053	1,644	2,032	2,092	2,391	2,709	3,915	4,526									
	kg	1,065	1,160	1,345	1,814	1,860	2,053	2,284	746	922	949	1,085	1,183	1,179	1,385	746	922	949	1,085	1,229	1,776	2,053									
WEIGHT																															
	lbs	403 *	484 *	772 *	1157	1642	1980	2853	214	231	256	287	383	438	859	227	242	282	317	480	1580	1758									
	kg	183 *	220 *	350 *	526	745	900	1297	97	105	116	130	174	199	390	103	110	128	144	218	717	799									
WITH BOW LOCKER	lbs								229	250	311	312	421	479		247	262	295	335	501											
	kg								104	113	141	142	191	217		112	119	134	152	227											
ENGINE																															
RECOMMENDED	hp	40	60	75	115	150	150	250	20	25	30	40	50	50	90	20	25	30	40	50	150	150									
	kW	29.8	44.8	56	85.8	111.9	111.9	186.5	14.9	18.7	22.4	29.8	37	37	67	14.9	18.7	22.4	29.8	37	111.9	111.9									
MAX	hp	50	75	90	150	225	250	500	30	30	40	50	60	70	115	30	30	40	50	60	200	250									
	kW	37.3	56	67	111.9	186.5	186.5	373.0	22.4	22.4	29.8	37	44.8	52.2	85.8	22.4	22.4	29.8	37	44.8	149	186.5									
SHAFT LENGTH	in	20"	20"	20"	25"	25"	25"	30"	20"	20"	20"	20"	20"	20"	25"	15"	15"	20"	20"	20"	25"	25"									
	cm	50.8	50.8	50.8	63.5	63.5	63.5	76.2	50.8	50.8	50.8	50.8	50.8	50.8	63.5	38.1	38.1	50.8	50.8	50.8	63.5	63.5									
MAX WEIGHT	lbs	253	330	365	515	683	814	1240	132	183	182	242	242	253	484	132	182	182	242	253	771	814									
	kg	115	150	166	234	310	370	564	60	83	83	110	110	115	220	60	83	83	110	115	350	370									
BUILT-IN TANKS																															
GAS	gal	N/A	27***	34***	49	63	65	189					16***	16***	32						55	59									
	lt	N/A	102***	128***	185	240	246	715					60***	60***	120						208	223									
WATER	gal																														
	lt																														
STOWED DIMENSIONS																															
LENGTHXWIDTHXHEIGHT	inch	156x49x28	169x59x43	192x54x47	213x75x32	238x81x36	276x87x35	323x113x47	132x44x19	138x46x26	144x47x32	159x47x32	167x47x32	182x55x32	214x71x38	132x44x19	138x46x26	144x47x32	159x47x32	182x55x32	234x83x38	270x83x38									
	cm	395x125x70	430x150x110	490x137x130	540x190x82	605x206x91	700x220x90	820x288x220	334x113x47	350x116x65	365x120x82	405x120x82	425x120x82	463x140x82	544x180x97	334x113x47	350x116x65	365x120x82	405x120x82	463x140x82	594x211x97	686x211x97									
RBC DESIGN CATEGORY																															
		C	C	C	C	C	B	B	C	C	C	C	C	C	C	C	C	C	C	C	C	C									

* WEIGHT SPEC APPLIES FOR THE OPEN VERSION

*** OPTIONAL FUEL TANK

FEATURES FOR THE F 14, F15 AND F 17 STATED ARE FOR THE OPEN VERSION

EPA COMPLIANT FUEL TANKS, 7% REDUCTION APPROXIMATELY



FEATURES	PROFILE F							PROFILE A							PROFILE AS					PROFILE A-XHD		
	F 14	F 15	F 17	F 19	F 21	F 24	F 28	A 11	A 12	A 13	A 14	A 15	A 16	A 18	A 11-S	A 12-S	A 13-S	A 14-S	A 16-S	A 21-XHD	A 24-XHD	
STANDARD FEATURES ●																						
OPTIONAL FEATURES ○																						
(CSM) COATED FABRIC 1670 D-TEX FABRIC	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
(CSM) COATED FABRIC NON-SKID ON TUBES	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
LED ALL AROUND ANCHOR LIGHT	○	○	○	●	●	●	●	○	○	○	○	○	○	○	○	○	○	○	○	●	●	
BENCH SEAT WITH STORAGE	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
BOW AND LATERAL REINFORCED COATED FABRIC HANDLES	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
BOW EYE - ALUMINUM								●	●	●	●	●	●	●	●	●	●	●	●	●	●	
BOW EYE - STAINLESS STEEL	●	●	●	●	●	●	●															
BOW SEAT WITH STORAGE	●	●	●	●	●	●	●	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
BOW SEAT WITH STORAGE & PORTABLE 6 GALLON FUEL TANK								○	○	○	○	○	○	○	○	○	○	○	○			
CARBON FIBER LOOK SWITCH WITH BRAKER BOARD				●	●	●	●															
CONSOLE ALUMINUM								○	○	○	○	○	○	○	○	○	○	○	○	○	○	○
CONSOLE WITH FORWARD SEAT	○	○	○	○	○	○	○			○	○	○	○	○	○	○	○	○	○	○	○	
DAVIT LIFTING RINGS - ALUMINUM								●	●	●	●	●	●	●	●	●	●	●	●	●	●	
DAVIT LIFTING RINGS - STAINLESS STEEL	●	●	●	●	○	○	○															
DOUBLE SOLID RUB RAIL	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
ENGINE GUARD	○	○	○	○	○	○	○						○	○					○	○	○	
FIBERGLASS BOW STEP WITH SS RETRACTING CLEAT	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
FIBERGLASS CONSOLE WITH WINDSHIELD AND RAIL	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
FUEL SENDING UNIT	○		○	○	○	○	○													●	●	
INTEGRATED ALUMINUM FUEL TANK		○	○	○	○	○	○					○	○	●						●	●	
FUEL/WATER SEPARATOR & CANISTER	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
HAND PUMP/REPAIR KIT	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
JOCKEY CONSOLE (1 PERSON)	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
JOCKEY CONSOLE (2 PERSON)	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
LEANING BOLSTER																				○	○	
LIFELINE AROUND TUBE	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
LIGHT ARCH	○		○	○	○	○	○													○	○	
LED NAVIGATION LIGHTS	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
NON SKID DECK - DIAMOND SHAPE	●	●	●	●	●																	
SEADEK® EVA FOAM NON-SKID FLOOR																						
SLIP RESISTANT SURFACE																				●	●	
PADDLES	●	●	●					●	●	●	●	●	●	●	●	●	●	●	●	●	●	
REINFORCED TRANSOM KNEES								●	●	●	●	●	●	●	●	●	●	●	●	●	●	●
RUBBER KEEL PROTECTOR	●	●						●	●	●	●	●	●	●	●	●	●	●	●			
WELDED ALUMINUM KEEL PROTECTOR															○						●	●
PRESSURE RELIEF VALVES	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
SIDE STEP/STAINLESS STEEL FOLD DOWN CLEAT	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	
TOWING POST - BOW				○	○	○	○	○						○						○	○	
TOWING POST - STERN				○	○	○	○	○													○	○
TOWING EYES - STERN (ALUMINUM)								●	●	●	●	●	●	●	●	●	●	●	●	●	●	
TOWING EYES - STERN (STAINLESS STEEL)	●	●	●	●	●	●	●															
TRANSOM ELEPHANT NOSE SCUPPERS (2 7/8 IN INTERNAL Ø)		●	●					●	●	●	●	●	●	●	●	●	●	●	●	●	●	
T-TOP				○	○	○	○								○						○	○
FULLY UPHOLSTERED SEATING SPRADLING®	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	○	

FOR ADDITIONAL INFORMATION AND LISTING OF WORLDWIDE DEALERS VISIT US AT ABINFLATABLES.COM